



Sales and Service of New and Used Wireline Trucks

1221 Barron Way  
Fort Worth, TX 76140  
Phone: 817-546-0772  
Fax: 817-568-0272

Email: [info@texaswireline.com](mailto:info@texaswireline.com)

## Tandem Axle Itemized Equipment List

### Standard features

Aluminum riveted body  
RS Locking operator's door  
Anodized aluminum interior  
Foam insulated operator's compartment  
Rubber safety flooring  
Lo-profile air conditioners  
Heater  
Recessed dual voltage ceiling lights  
Power enclosure cabinet (CS)  
AM/FM/CD stereo  
Upper storage cabinet (RS)  
Dual lower storage cabinets  
Fully instrumented operators console  
Digital Murphy power view system  
Multiple outlets including 12V for cell phone  
Fire extinguisher and first aid kit  
High-density foam customer bench w/storage  
Large sliding safety-glass operator window  
Large safety-glass window in door  
Pull out self-storing steps  
Isolated chassis to body mounting system  
Rubber runners length of body  
Full-length underbody tool trough w/airbags  
Dual upper tool racks, 1 short & 1 long (airbags optional)  
Universal reel mounts (holds drums from 850-1050)  
Safety placards (4)  
DOT LED lighting  
Lights-storage compartments, step, and drum  
Remote control rear/rig lights  
Safety alarms  
4 built-in locking outer storage compartments  
30Kw Marathon generator  
Single color full body paint  
Heavy-duty front bumper  
Heavy-duty rear bumper w/storage, vise and folding step

### Draw works

3-speed Funk transmission w/planetary drive  
Single drum/split drum  
Geo-Log measuring head w/parallel arm,  
10K Martin Decker w/mechanical counter  
Rexroth hydraulics  
40 gal hydraulic tank  
Hydraulic cooler w/fan  
High-strength canvas cover  
Line oiler tank assembly w/spray bar  
Heavy duty Muncie PTO and driveline  
Parker hoses  
Donaldson spin-on filters

### Options

Marlite wall panels  
Wall-mounted cabinets  
Secondary cabinet under enclosure  
Light table (portable or built-in)  
Logo decals  
System Rack  
Locking underbody tool tray door  
Rear compartment panels  
OH measuring system  
Sheave wheel brackets  
Grease injection system (10K PSI)  
Heated hydraulic tank

### Body Specifications

OAL: 270 in  
OAW: 95 in  
Int Clr: 79 in